

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 January 2004 (29.01.2004)

PCT

(10) International Publication Number
WO 2004/009498 A1

(51) International Patent Classification⁷: C02F 1/46, 1/461

(21) International Application Number:
PCT/GB2003/003540

(22) International Filing Date: 21 July 2003 (21.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0217268.2 23 July 2002 (23.07.2002) GB

(71) Applicant and

(72) Inventor: CROSS, David, Edward [GB/GB]; Hedge
End, Hurst Road, East Preston, Littlehampton, West
Sussex BN16 3AP (GB).

(74) Agent: COLES, Graham, Frederick; Graham Coles &
Co, 24 Seeleys Road, Beaconsfield, Buckinghamshire HP9
1SZ (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: ELECTROCHEMICAL CELLS



(57) Abstract: An electrochemical cell has an inner, titanium-rod electrode (1) mounted coaxially within an outer, titanium-tube electrode (2) with a porous, ceramic tube (3) mounted coaxially between them to define coaxial, annular passageways (4,5) for liquid flow in separate streams lengthwise of the cell between respective pairs of inlet/outlet ports (6, 6; 7, 7). A cup-shape fitting (8) having a stepped-down internal diameter is clamped onto the rod electrode (1) at each end of the cell, with the tubular electrode (2) at that end held tightly sealed in the mouth (14) of the fitting (8). Each end of the ceramic tube (3) projects into the larger-diameter cavity-part (10) of the fitting (8) at that end and has a radial flange (17) that provides a sliding seal within this cavity-part (10) for keeping the inlet/outlet ports (6,7) for the respective liquid streams at that end, divided off from one another as well as allowing the ceramic tube (3) limited freedom for longitudinal sliding relative to the electrodes (1, 2).

1/PRTS

10/521951

DT01 Rec'd PCT/PTC 21 JAN 2005

Electrochemical Cells

This invention relates to electrochemical cells.

5 The invention is particularly, though not exclusively,
concerned with electrochemical cells of the kind used for
purification of water and the production of disinfecting
aqueous solutions. Electrochemical cells of this kind
10 have been proposed in which an ion-permeable, ceramic
membrane is interposed between coaxial electrodes, and it
is one of the object of the present invention to provide
an improved form of such a cell.

15 According to the present invention there is provided an
electrochemical cell in which an inner cylindrical
electrode extends coaxially within a tube of ion-
permeable material that is mounted coaxially within a
hollow, cylindrical outer electrode to define inner and
20 outer annular passageways between the respective
electrodes and said tube for liquid-flow lengthwise of
them from one to the other of cup-shape fittings at
either end of the cell, each cup-shape fitting having two
inlet/outlet ports that communicate with the inner and
outer passageways respectively, wherein each cup-shape
25 fitting defines a cylindrical cavity which has an open-
mouth that is of a diameter to receive a respective end
of the outer electrode for liquid-tight sealing
therewith, said tube projects at each end of the cell
from within the outer electrode into said cavity of the
30 fitting at that end and has an annular rim for engagement
with an internal cylindrical wall of the cavity for
liquid-tight sealing therewith to separate the inner and
outer passageways from one another within the fitting,
and the inner electrode projects at each end of the cell
35 from said tube into the cavity of the fitting at that
end.

each fitting may open into/from the first and second cavity-parts respectively.

5 An electrochemical cell in accordance with the present invention will now be described, by way of example, with reference to the accompanying drawing, in which:

10 Figure 1 is a part sectional side-elevation of the electrochemical cell according to the invention; and

Figure 2 is an enlarged sectional side-elevation of one end of the electrochemical cell of Figure 1.

15 Referring to Figures 1 and 2, the inner and outer electrodes of the electrochemical cell are formed by a coaxial rod 1 and tube 2 respectively. The rod 1 and tube 2 are of titanium and the inside surface of the tube 2, which is to act as the anode, is coated with ruthenium and iridium oxides that act as a catalyst in the
20 electrochemical operation of the cell. A porous ceramic tube 3 composed of aluminium, zirconium and yttrium oxides, is supported coaxially between the rod 1 and tube 2 to provide an intermediate ion-permeable membrane for separating the products derived electrochemically at the
25 two electrodes. More particularly, the tube 3 divides the space between the rod 1 and tube 2 into two coaxial, annular passageways 4 and 5 for liquid-flow lengthwise of the electrodes formed by the rod 1 and tube 2.

30 The passageways 4 and 5 terminate at either end of the cell in sideways-extended inlet/outlet ports 6 and 7, respectively, of individual one-piece plastics fittings 8 (for example, of polypropylene) that are retained on opposite ends 9 of the rod 1. Each fitting 8 is of cup-
35 shape with a stepped internal diameter that defines a first cylindrical cavity-part 10 into/from which the port 7 opens, and which leads via an annular end-face 11

(Figure 2) into a second cylindrical cavity-part 12 of smaller diameter into/from which the port 6 opens. The ends 13 of the tube 2 are lightly machined externally over a short length (for example, 5 mm) so as to enable
5 them to be received and provide liquid-tight sealing, in recessed mouths 14 (Figure 2) of the cavity-parts 10 of the fittings 8.

The rod 1, on the other hand, extends axially through
10 both cavity-parts 10 and 12 of each fitting 8, and has ends 9 of reduced diameter. The end 9 within each fitting 8 projects from the cavity-part 12 into and through a bore 15 of the fitting 8. It is a liquid-tight interference fit within the bore 15 (it may be lightly
15 machined over a length of, for example, 5 mm, to ensure a constant diameter for the purpose), and is screw-threaded to receive a nut 16 (only one shown, in Figure 1) where it projects from the fitting 8. The nuts 16 are
20 tightened to clamp the fittings 8 firmly onto the two ends 13 of the tube 2 and hold them to the rod 1 with the rod 1 and tube 2 coaxial with one another.

The tube 3, which projects beyond the ends 13 of the tube 2 within the cavity-part 10, has a radial rim or flange
25 17 (Figure 2) at each end. Each flange 17 is part of a plastics tubular moulding 18 which is retained on the tube 3 by a plastics sleeve 19 that is heat-shrunk onto the respective end of the tube 3; the dimensioning of the moulding 18 allows for manufacturing tolerances in tube-
30 diameter. The flange 17 provides a liquid-tight, sliding fit within the internal cylindrical wall of the respective cavity-part 10, separating the passageways 4 and 5 from one another within the fitting 8 at that end.

35 More especially, the extent of projection of the tube 3 beyond the end 13 of the tube 2 within each fitting 8 ensures that the flange 17 is located deeper within the

cavity-part 10 than the port 7 so that it maintains appropriate separation of the port 7 from the cavity-part 12 and port 6. The integrity of this separation is maintained since the freedom of the tube 3 to slide
5 relative to the tube 2 is limited to a small distance (for example, 1 to 2 mm) by the walls 11 at both ends of the cell. However, the freedom for sliding ensures that the clamping forces exerted by the nuts 16 clamping the fittings 8 to the ends 13 of the tube 2 and holding them
10 on the ends 9 of the rod 1, are not exerted on the tube 3. The fact that the somewhat-fragile, ceramic tube 3 is not subject to any clamping force avoids the need to cushion it resiliently.

15 The attachment of the mouldings 18 to the tube 3 may be by adhesive instead of the heat-shrunk sleeves 19, or by bonding them on by heating the ends of the tube 3 so that the plastics is partially melted as the mouldings 18 are pushed on.

20 The form of construction of the electrochemical cell described above, has significant advantages of simplicity and economy in that the number of components is reduced as compared with earlier forms, and the extent of
25 machining required is light and limited to the ends 9 of the rod 1 and the ends 13 of the tube 2. Moreover, stock material may be used for the electrodes (for example seam-welded tubing may be used for the tube 2), and the porous ceramic tube 3, which for example, may have a
30 porosity between 50% and 70% with a pore size of between 0.3 and 0.5 microns, is not required to withstand compressional forces or satisfy tight dimensional tolerance-limits. The flanges 17 of the mouldings 18 attached to the ends of the tube 3 provide both the
35 sliding freedom and the liquid-tight sealing required, in a simple manner without any strict dimensional requirement on tube-diameter.

Claims:

1. An electrochemical cell in which an inner cylindrical electrode extends coaxially within a tube of ion-permeable material that is mounted coaxially within a hollow, cylindrical outer electrode to define inner and outer annular passageways between the respective electrodes and said tube for liquid-flow lengthwise of them from one to the other of cup-shape fittings at either end of the cell, each cup-shape fitting having two inlet/outlet ports that communicate with the inner and outer passageways respectively, wherein each cup-shape fitting defines a cylindrical cavity which has an open-mouth that is of a diameter to receive a respective end of the outer electrode for liquid-tight sealing therewith, said tube projects at each end of the cell from within the outer electrode into said cavity of the fitting at that end and has an annular rim for engagement with an internal cylindrical wall of the cavity for liquid-tight sealing therewith to separate the inner and outer passageways from one another within the fitting, and the inner electrode projects at each end of the cell from said tube into the cavity of the fitting at that end.
2. An electrochemical cell according to Claim 1 wherein the outer electrode is a metal tube.
3. An electrochemical cell according to Claim 1 or Claim 2 wherein the inner electrode is a metal rod.
4. An electrochemical cell according to any one of Claims 1 to 3 wherein the particular one of the electrodes that is to act as the cathode of the cell, is of titanium or stainless steel.

5. An electrochemical cell according to any one of Claims 1 to 4 wherein the particular one of the electrodes that is to act as the anode of the cell is of titanium.

6. An electrochemical cell according to Claim 5 wherein the anode electrode has a coating that acts as a catalyst in the electrochemical operation of the cell.

7. An electrochemical cell according to Claim 6 wherein the coating of the anode electrode is of ruthenium and iridium oxides.

8. An electrochemical cell according to any one of Claims 1 to 7 wherein the ion-permeable tube is of a porous ceramic material.

9. An electrochemical cell according to Claim 8 wherein the ceramic material is composed of aluminium, zirconium and yttrium oxides.

10. An electrochemical cell according to any one of Claims 1 to 9 wherein the annular rim at each end of the cell is slidable within the cavity of the fitting at that end to enable sliding of the ion-permeable tube relative to the inner and outer electrodes.

11. An electrochemical cell according to Claim 10 wherein the annular rim at each end of the cell comprises a flange of a member that is sealed or otherwise secured to the ion-permeable tube at that end.

12. An electrochemical cell according to Claim 10 or Claim 11 wherein the extent to which the ion-permeable tube can slide relative to the inner and outer electrodes is limited by abutment within the cavity at each end of the cell.

13. An electrochemical cell according to any one of Claims 1 to 12 wherein the cavity of each cup-shape fitting has a stepped internal diameter for defining a first cavity-part leading from the open mouth and a second cavity-part of smaller diameter opening from the first cavity-part.

14. An electrochemical cell according to Claim 13 wherein the ion-permeable tube projects at each end of the cell from within the outer electrode into the first cavity-part of the fitting at that end to have its annular rim engage with the internal cylindrical wall of the first cavity-part, and the inlet/outlet ports of each fitting open into/from the first and second cavity-parts respectively.

10/521951

1/1




Fig. 1




Fig. 2

INTERNATIONAL SEARCH REPORT

International Application No
PCT/JP 03/03540

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 C02F1/46 C02F1/461

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 C02F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 58880 A (STERILOX TECH INT LTD ;POPOV ALEXEY YURIEVICH (RU); POPOV DMITRIY) 30 December 1998 (1998-12-30) claim 1; figure 1	1,2,4,8, 10-14
X	US 4 810 344 A (OKAZAKI TATSUO) 7 March 1989 (1989-03-07) column 4, line 16-23; figure 1	1-6
X	US 673 452 A (ROBERTS I L) 7 May 1901 (1901-05-07) figures	1-3

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

2 December 2003

Date of mailing of the international search report

19/12/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Serra, R

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 03/03540

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 9858880	A	30-12-1998	RU	2132821 C1	10-07-1999
			AU	8223998 A	04-01-1999
			WO	9858880 A1	30-12-1998
US 4810344	A	07-03-1989	JP	1056188 A	03-03-1989
			DE	3867284 D1	13-02-1992
			EP	0286233 A2	12-10-1988
			KR	9600302 B1	04-01-1996
US 673452	A		NONE		